

Serial No.: 10/686,177
Office Action Date: 8/27/2004

Filed: 10/14/2003
Amendment Date: 10/27/2004

Amendments to the Specification

[0032] To the left of the shift ratio line 91 is a preferred region of operation 93 for the first mode wherein C1 is applied and C2 is released. To the right of the shift ratio line 91 is a preferred region of operation 95 for the second mode wherein C1 is released and C2 is applied. When used herein with respect to clutches C1 and C2, the term applied indicates substantial torque transfer capacity across the respective clutch while the term released indicates insubstantial torque transfer capacity across the respective clutch. Since it is generally preferred to cause shifts from one mode to the other to occur synchronously, torque transfers from one mode into the other mode are caused to occur through a two clutch application fixed-ratio wherein, for a finite period prior to the release of the presently applied clutch, the presently released clutch is applied. And, the mode change is completed when fixed-ratio is exited by the continued application of the clutch associated with the mode being entered and the release of the clutch associated with the mode being exited. While region of operation 93 is generally preferred for the operation of the EVT in MODE 1, it is not meant to imply that MODE 2 operation of the EVT cannot or does not occur therein. Generally, however, it is preferred to operate in MODE 1 in region 93 because MODE 1 preferably employs gearsets and motor hardware particularly well suited in various aspects (e.g. mass, size, cost, inertial capabilities, etc.) to the high launch torques of region 93. Similarly, while region of operation 95 is generally preferred for the operation of the EVT in MODE 2, it is not meant to imply that MODE 1 operation of the EVT cannot or does not occur therein. Generally, however, it is preferred to operate in MODE 2 in region 95 because MODE 2 preferably employs gearsets and motor hardware particularly well suited in various aspects (e.g. mass, size, cost, inertial capabilities, etc.) to the high speeds of region **[93]** 95. A shift into MODE 1 is considered a downshift and is associated with a higher gear ratio in accordance with the relationship of Ni/No. Likewise, a shift into MODE 2 is considered an upshift and is associated with a lower gear ratio in accordance with the relationship of Ni/No.

GMC3148

2 of 10